

## **Industrial Bag Closing Machine NEWLONG DS-6AC**

Automatic, single needle machine for closing bags with sewing.
When tightly closed bags are required (for dusty, powdery materials), the machine can be equipped with crepe tape adaptor.

The machine switches on and off automatically using either microswitch control lever or photo cell switch, which is activated by inserting the bag to the machine against the switch. The same way, when the bag leaves, the machine is deactivated by another photo cell switch. At the same time the thread and ev. also the crepe tape are cut off.

The parametres of the NL DS-6AC machine:

Maximal speed: 1400 stitches per min. Maximal thickness of the material: 10 mm

Presser foot clearance: 62mm

Stitch width: 7 – 10,5 mm (standard set up: 10 mm) Stitch type: single needle, double chain stitch Way of bag closing: sewing or crepe tape sewing Cut off type: Built in air cylinder operated cutter Lubrication system: Manual oil feed & oiler

Type of thread: Synthetic or cotton

Needle type: DRx2 # 25

Required type of motor: 0,4kW, 4P, 3phase – is not part of the delivery, should be ordered separately.

Way of packing: Total weight: 39kg

Dimensions: 53x36x550,1

Volume: 0,1 m<sup>3</sup>

We offer also all materials for bag closing: threads, needles, oil, polypropylene and raschel bags in wide scale of dimensions and colours.

The machine should be used for closing of paper bags and all types of woven bags.

Extremely durable machine for work in difficult conditions. Low requirements on maintanance, service, spare parts.

## NEWLOND -

## Advantages of NEWLONG DS-6AC:

High quality product made in Japan. Durable, reliable

User friendly, high speed of sewing. High labour productivity. Low cost.

Universal machine for closing all sorts of bags.

Full assortment of accessories and consumer material (threads, needles, bags) available for prompt delivery.